



FULL SENA SPECIFICATIONS FOR THE NOTCH HOOKUPS

Work4 | 10S SPECIFICATIONS

GENERAL

DIMENSIONS

- Main Module: 85 mm x 57 mm x 27 mm (3.4 in x 2.2 in x 1.1 in)
- Speaker Driver Unit: 40 mm—thickness 6.5 mm
- Boom Microphone: length 183 mm

WEIGHT

- Main Module: 58 g (2.05 oz)
- Operating Temperature: -10 °C – 55 °C (14 °F – 131 °F)

BLUETOOTH

Bluetooth 5.1
Headset Profile (HSP)
Hands-Free Profile (HFP)
Advanced Audio Distribution Profile (A2DP)
Audio Video Remote Control Profile (AVRCP)

INTERCOM

Working Distance: up to 1.6 km (1 mile) in open terrain
Supports: up to 4 crew members

AUDIO

Noise Cancellation: Advanced Noise Control™
Codec: Built-in SBC Codec
HD Voice enabled for high-quality phone call audio

BATTERY

Talk Time: up to 12 hours
Charging Time: 3 hours
Type: Lithium Polymer Battery

CERTIFICATES

CE, FCC, IC



FULL SENA SPECIFICATIONS FOR THE NOTCH HOOKUPS

33i | 30k SPECIFICATIONS

GENERAL

DIMENSIONS

- Main Module: 102 mm x 56 mm x 27 mm (4.0 in x 2.2 in x 1.1 in)
- Speaker Driver Unit: 40 mm—thickness 6.5 mm
- Boom Microphone: length 190 mm
- Wire Between Speakers: length 555 mm

WEIGHT

- Main Module: 61 g (2.15 oz)
- Operating Temperature: -10 °C – 55 °C (14 °F – 131 °F)

MESH NETWORK

Mesh Intercom™ Technology

BLUETOOTH

Bluetooth 5.0

Headset Profile (HSP)

Hands-Free Profile (HFP)

Advanced Audio Distribution Profile (A2DP)

Audio Video Remote Control Profile (AVRCP)

INTERCOM

Working Distance:

- Bluetooth Intercom: up to 2 km (1.2 miles) in open terrain
- Mesh Intercom™: up to 2 km (1.2 miles)* in open terrain

*Can extend up to 8 km (5 miles) between a minimum of 6 crew members

SUPPORTS UP TO:

- Bluetooth Intercom: 4 crew members
- Open Mesh Intercom: virtually limitless
- Group Mesh Intercom: 24 crew members

SUPPORTS CHANNELS:

- Open Mesh Intercom: 9 channels

AUDIO

Noise Cancellation: Advanced Noise Control™

Codec: Built-in SBC Codec

HD Speakers

Aux Out: 3.5 mm Port

BATTERY

Talk Time:

- Bluetooth Intercom: up to 11 hours
- Mesh Intercom™: up to 10 hours

Charging Time: 2.5 hours

Quick Charging: 20 minutes of charging equals 2 hours Bluetooth intercom or 2 hours Mesh Intercom

Charging Temperature: 0 °C – 45 °C (32 °F – 113 °F)

Type: Lithium Polymer Battery

CERTIFICATES

CE, FCC, IC

WARRANTY

2-Year Warranty

NOTCH